
SMART SOLUTIONS FOR WATER RE-USE

UNIBIOLINE CNL XR







TECHNICAL DATA

UNIBIOLINE CNL XR

UNIQUE DESIGN

11 EXTERIOR

The exterior has been designed with a chemical free root intrusion barrier by incorporating Copper Oxide in the mold of the diaphragm cover.



2 INTERIOR

The interior has been designed to allow water to flow without being blocked by fine feeder roots or by sediment built-up in the dripperline.



| DRIPPER TECHNICAL DATA | | | | | | |
|------------------------|--------------|-----------|-----------------|------------------|----------------|----------------|
| FLOW RATE | DRIPPER NAME | PACKAGING | INSIDE DIAMETER | OUTSIDE DIAMETER | WALL THICKNESS | PRESSURE RANGE |
| L/HR | | | ММ | ММ | ММ | M |
| 1.0, 1.6, 2.3 & 3.5 | UniRam™ CNL | Strapped | 14.2 | 16.2 | 1.0 | 10 – 35* |

^{*} The Uniram CNL emitter will function at 10m but for waste water we recommend a minimum of 12m.

| TECHNICAL DATA & PRODUCT CODES | | | | | | | |
|--------------------------------|-----------|-----------------|-------------|---------|---------|---------|---------|
| CODE | FLOW RATE | DRIPPER SPACING | COIL LENGTH | 150 KPA | 200 KPA | 250 KPA | 300 KPA |
| | L/HR | М | M | M | M | M | M |
| 13964-002000 | 1.6 | 0.4 | 200 | 100 | 128 | 148 | 160 |
| TBA | 1.6 | 0.5 | 100 | 122 | 156 | 179 | 198 |
| ТВА | 2.3 | 0.4 | 200 | 81 | 102 | 116 | 130 |
| TBA | 2.3 | 0.5 | 400 | 98 | 124 | 143 | 156 |
| TBA | 2.3 | 0.6 | 100 | 112 | 143 | 165 | 181 |
| TBA | 3.5 | 1.0 | 100 | 129 | 165 | 190 | 210 |

Maximum run length (m) for single lateral on flat ground to achieve 10m at the end of the lateral.

| SUITABLE FITTINGS | | | | | |
|-------------------|---|--------------|---|--|--|
| PRODUCT CODE | DESCRIPTION | PRODUCT CODE | DESCRIPTION | | |
| | | | | | |
| 32500-013750 | 16mm Start Take-off to suit LDPE | 32500-012500 | 16mm Elbow | | |
| 00005-011500 | 16mm Elbow Take-off to suit 16mm LDPE | 32500-001130 | 16mm Tee | | |
| 45000-001650 | 7mm Professional Punch Tool | 32500-010700 | 16mm Joiner | | |
| 32500-013700 | 16mm Straight Take-off with Grommet to suit PVC | 76400-011750 | 16mm Herbie Clip Ratchet Clamp | | |
| 00025-002400 | Hold Down Stake (Asta) | 00005-002200 | 16mm Ratchet Clamp | | |
| 00005-010600 | 19mm x 16mm Barbed Elbow | 00060-006020 | 16mm Stainless Steel Netafim Clamp (15/8) | | |

SMART SOLUTIONS FOR WATER RE-USE

CHEMICAL FREE RESISTANCE TO ROOT INTRUSION

UNIBIOLINE CNL XR

Netafim's UniBioline CNL XR provides a unique cost effective solution to combat root intrusion.

The diaphragm cover is impregnated with Copper Oxide as part of the mould.

This means it does not deteriorate; giving you peace of mind that your plants are still getting the exact amount of water they need, where and when they need it.

- Effective for the life of your dripperline
- No replacement of chemical injected filter units
- Reduced maintenance costs

GROW MORE WITH LESS®

XR

WWW.NETAFIM.COM.AU

